



## General

Built	November-1993	International	<b>GT</b> 7,326.00	<b>NT</b> 4,810.00
Flag	Liberia	Panama Canal		6,657.00
Port of Registry	Monrovia	Suez Canal		6,503.21
Callsign	A8OE5			
IMO/Lloyds nr	9047271		<b>Draft</b>	<b>DWAT</b>
Length over all [m]	134.02	Tropical	7.72	8,365
Beam [m]	20.80	Summer	7.57	8,041
Depth [m]	10.17	Winter	7.42	7,723
Bowthruster(s)	-			

## Reefer

Holds	4
Hatches	4
Compartments	15
Minimum Deckheight [m]	2.20
Allowable weight of forklift including cargo	maximum 5 mt (Forklift to be equipped with minimum 4 airtyres)
Temperature zones	8
Cooling sections	1A   1BC   2AB   2CD   3AB   3CD   4AB   4CD
Temperature range [dC]	-30/+15
Air circulations [/hr]	90
Air renewals [/hr]	4
USDA equipped	Yes, certificate expired
Controlled Atmosphere	None
Modified Atmosphere	No equipment on board

## Classification Details

Classification Society	American Bureau Of Shipping (ABS)
Class Notations	A1, Vehicle Carrier, AMS, CA, RMC
Additional Notations	CRC
Service Limit	Unrestricted Service
Equivalent Finnish/Swedish Ice Strengthening	-

**Reefer Compartment Capacity Breakdown**

	Hold 1		Hold 2		Hold 3		Hold 4		Total	
	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm
A	30,048	340.85	20,569	228.12	20,438	229.59	23,714	267.46	94,769	1,066.02
B	19,090	227.30	30,875	345.89	34,494	371.23	38,662	421.78	123,122	1,366.20
C	13,966	163.27	28,378	340.93	32,265	390.72	31,418	355.05	106,028	1,249.97
D			23,189	270.18	30,328	354.83	23,449	237.07	76,966	862.08
Total	63,105	731.42	103,011	1,185.12	117,525	1,346.37	117,243	1,281.36	400,884	4,544.27

**Hatch sizes**

	Hold 1	Hold 2	Hold 3	Hold 4
	l x b	l x b	l x b	l x b
Deck	7.40 x 7.30	7.40 x 7.30	7.40 x 7.30	7.40 x 7.30
A	7.40 x 7.30	7.40 x 7.30	7.40 x 7.30	7.40 x 7.30
B	7.40 x 4.90	7.40 x 7.30	7.40 x 7.30	7.40 x 7.30
C		7.40 x 7.30	7.40 x 7.30	7.40 x 7.30

Container Carrying Capacity	Max FEU's	Add. TEU's	Max TEU's	Add. FEU's	
<u>On Weather Deck and Hatches</u>					
Empty Positions	Standard	6	0	12	0
Max Stackweight	Standard	6	0	12	0
Max Stackweight - Self-sustained	Standard	0	0	0	0
<u>Reefer Hold</u>					
Empty Positions	Standard	0	0	0	0
Max Stackweight	Standard	0	0	0	0
Max Stackweight - Self-sustained	Standard	0	0	0	0

'Max Stackweight' and 'Max Stackweight - Self-sustained' are the number of laden containers that can be loaded basis the maximum stackweight, calculating 26 mt gross for a laden FEU and 14 mt gross for a laden TEU

Above figures are as per vessel's technical layout. Actual container intake is subject to master's approval and depending on stability, stackweight and visibility.

**Standard Voyage Container Carrying Capacity**

Nr of High Cube (9.5') Reefers 6  
of which Self-sustained 0

'Standard Voyage' = voyage from Panama Canal to Rotterdam, with a full cargo of bananas in the holds and departing with full bunker tanks. Containers on this voyage are considered to weigh 26 mt gross.

**Reefer Plugs**

Nr. of electrical Reefer Plugs 12

**Cargo Gear**

8 Derricks x 5.0 mt or 4 x 3.5 mt in Union Purchase

- All peeds are 'about', all consumptions are 'about', basis clean hull, clean propeller and deep (minimum 7 x deepest draft), currentless water/sea with a temperature of maximum 28 degree Celcius.
- Descriptions are given basis maximum Beaufort 4, maximum 2 meters swell and maximum 2 meters wave height.
- Additional MGO may be used for starting/stopping engines and/or manouvring and/or in narrow and/or restricted waters and/or in extreme weather conditions.
- All auxiliary consumptions are based on maintaining cargo temperatures, during reduction period higher consumptions may be recorded.
- All descriptions exclude consumption for carried laden reefer containers. Depending on ao the make and/or type of container, maintenance state of the container, commodity in the container, ambient temperature, use of water cooling, stowage position: as indication an average additional fuel consumption of about 30 kg/container/24hrs when maintaining temperatures to be taken into account.
- Port consumptions are averages for vessel lying alongside berth. Manoevring consumptions are excluded.
- Auxiliary consumption up to 6 mt/day with all generators fully loaded.
- All Speeds are in knots and all consumptions are in metric tons per 24 hours.
- International and/or local regulations may require use of other fuel grades.
- Conditions are based on sailing with even keel, unless stated otherwise. Significant trim, especially large negative trim, may have negative impact on the performance.
- All consumption figures are based on ISO 8217 (latest revision) specification fuels with following minimum caloric values:  
 HFO: 40.600 kJ/kg  
 MGO 42.700 kJ/kg

## Bunker Tank Capacities

	<u>Cbm (100%)</u>	<u>Cbm at max filling level*</u>	<u>mt**</u>
Bunkertanks dedicated for High Sulphur RMG380 (IFO380)	814	692	686
Bunkertanks dedicated for Low Sulphur RMG380 (IFO380)	177	150	149
<b>Total bunker capacity for RMG380 (IFO380)</b>	<b>991</b>	<b>842</b>	<b>835</b>
Bunkertanks dedicated for High Sulphur DMB (MDO)	87	74	63
<b>Total bunker capacity for DMB (MDO)</b>	<b>87</b>	<b>74</b>	<b>63</b>
Bunkertanks dedicated for Low Sulphur DMA (MGO)	87	74	63
<b>Total bunker capacity for DMA (MGO)</b>	<b>87</b>	<b>74</b>	<b>63</b>

\*) Vessel shall not mix bunkers from different bunkerings in 1 bunker tank. This may reduce the actual bunker capacity.

\*\*) Capacity in mt serve as indication only. Actual capacity in mt depending ao on the specifice gravity and temperature of the supplied bunkers.

Vessel to be solely supplied with fuels as per ISO 8217:2010 or any subsequent amendment thereof. All supplied fuels shall be suitable to enable main propulsion and auxiliary machinery to operate efficiently and without harmful effects and in line with any national and/or international requirements. Fuels to be mineral based products and shall not contain waste lubricants (ULO), chemicals or any other harmful substances and shall be of homogenous and stable nature. Charterers to buy and arrange bunkers only from qualified suppliers and/or from majors and carry out their own quality checks as deemed necessary for their control.

Charterers warrant that whenever bunkers are ordered for the vessel, the order not to put a lien on the vessel and explicitly request "The Products shall not include waste chemicals, waste lubricants and/or other non-fuel components."

BIMCO Bunker Fuel Sulphur Content clause for Time Charter parties 2004 to apply.

If vessel is redelivered in an ECA area, Charterers warrant that vessel will be redelivered with sufficient bunkers suitable for consumption as per the requirements of the relevant ECA area to reach a port or place where suitable bunkers may be supplied.

Vessel participates in fuel testing program. Samples are taken during each fuel from each supplied grade. Costs involved to be equally shared between Owners and Charterers. Vessel shall not consume any supplied fuel without having received full fuel analysis report confirming the fuel's quality.

