



General

Built	January-1993	International	GT	NT
Flag	Liberia	Panama Canal	6,363.00	4,297.00
Port of Registry	Monrovia	Suez Canal		5,696.37
Callsign	A8JI5			5,573.44
IMO/Lloyds nr	9014444		Draft	DWAT
Length over all [m]	130.50	Tropical	7.93	7,690
Beam [m]	19.00	Summer	7.77	7,387
Depth [m]	10.10	Winter	7.61	7,087
Bowthruster(s)	1			

Reefer

Holds	4
Hatches	4
Compartments	15
Minimum Deckheight [m]	2.20
Allowable weight of forklift including cargo	maximum 5 mt (Forklift to be equipped with minimum 4 airtyres)
Temperature zones	8
Cooling sections	1A 1BC 2AB 2CD 3AB 3CD 4AB 4CD
Temperature range [dC]	-30/+15
Air circulations [/hr]	90
Air renewals [/hr]	4
USDA equipped	Yes, valid until 15-December-2018
Controlled Atmosphere	None
Modified Atmosphere	No equipment on board

Classification Details

Classification Society	Bureau Veritas (BV)
Main Class symbols	I, +HULL, +MACH
Service Notations	+Refrigerated cargo ship
Navigation Notations	Unrestricted Navigation
Additional Class Notations	+RMC
Machinery	+MACH
Equivalent Finnish/Swedish	
Ice Strengthening	-

Reefer Compartment Capacity Breakdown

	Hold 1		Hold 2		Hold 3		Hold 4		Total	
	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm
A	30,348	331.00	15,355	184.00	13,568	166.00	15,309	187.00	74,580	868.00
B	23,755	240.00	31,218	340.00	29,630	330.00	31,135	355.00	115,738	1,265.00
C	18,304	196.00	29,276	338.00	28,000	331.00	28,510	320.00	104,090	1,185.00
D			25,429	265.00	27,993	297.00	23,582	241.00	77,004	803.00
Total	72,407	767.00	101,278	1,127.00	99,191	1,124.00	98,536	1,103.00	371,412	4,121.00

Hatch sizes

	Hold 1	Hold 2	Hold 3	Hold 4
	l x b	l x b	l x b	l x b
Deck	6.20 x 7.40	6.20 x 7.40	6.20 x 7.40	6.20 x 7.40
A				
B				
C				

Container Carrying Capacity	Max FEU's	Add. TEU's	Max TEU's	Add. FEU's
On Weather Deck and Hatches				
Empty Positions Standard	49	2	60	3
Max Stackweight Standard	45	0	42	0
Max Stackweight - Self-sustained Standard	28	0	28	0
Empty Positions High Cube	49	2	60	3
Max Stackweight High Cube	45	0	42	0
Max Stackweight - Self-sustained High Cube	28	0	28	0
Reefer Hold				
Empty Positions Standard	0	0	0	0
Max Stackweight Standard	0	0	0	0
Max Stackweight - Self-sustained Standard	0	0	0	0

'Max Stackweight' and 'Max Stackweight - Self-sustained' are the number of laden containers that can be loaded basis the maximum stackweight, calculating 26 mt gross for a laden FEU and 14 mt gross for a laden TEU

Above figures are as per vessel's technical layout. Actual container intake is subject to master's approval and depending on stability, stackweight and visibility.

Standard Voyage Container Carrying Capacity

Nr of High Cube (9.5') Reefers	32
of which Selfsustained	23

'Standard Voyage' = voyage from Panama Canal to Rotterdam, with a full cargo of bananas in the holds and departing with full bunker tanks. Containers on this voyage are considered to weigh 26 mt gross.

Reefer Plugs

Nr. of electrical Reefer Plugs	47
--------------------------------	----

Cargo Gear

1 Crane x 36.0 mt

8 Derricks x 5.0 mt or 4 x 5.0 mt in Union Purchase

- All peeds are 'about', all consumptions are 'about', basis clean hull, clean propeller and deep (minimum 7 x deepest draft), currentless water/sea with a temperature of maximum 28 degree Celcius.
- Descriptions are given basis maximum Beaufort 4, maximum 2 meters swell and maximum 2 meters wave height.
- Additional MGO may be used for starting/stopping engines and/or manoeuvring and/or in narrow and/or restricted waters and/or in extreme weather conditions.
- All auxiliary consumptions are based on maintaining cargo temperatures, during reduction period higher consumptions may be recorded.
- All descriptions exclude consumption for carried laden reefer containers. Depending on ao the make and/or type of container, maintenance state of the container, commodity in the container, ambient temperature, use of water cooling, stowage position: as indication an average additional fuel consumption of about 30 kg/container/24hrs when maintaining temperatures to be taken into account.
- Port consumptions are averages for vessel lying alongside berth. Manoevring consumptions are excluded.
- Auxiliary consumption up to 6 mt/day with all generators fully loaded.
- All Speeds are in knots and all consumptions are in metric tons per 24 hours.
- International and/or local regulations may require use of other fuel grades.
- Conditions are based on sailing with even keel, unless stated otherwise. Significant trim, especially large negative trim, may have negative impact on the performance.
- All consumption figures are based on ISO 8217 (latest revision) specification fuels with following minimum caloric values:
 - HFO: 40.600 kJ/kg
 - MGO 42.700 kJ/kg

Bunker Tank Capacities

	<u>Cbm (100%)</u>	<u>Cbm at max filling level*</u>	<u>mt**</u>
Bunkertanks dedicated for High Sulphur RMG380 (IFO380)	768	653	647
Bunkertanks dedicated for Low Sulphur RMG380 (IFO380)	186	158	156
Total bunker capacity for RMG380 (IFO380)	954	811	803
Bunkertanks dedicated for High Sulphur DMB (MDO)	92	78	67
Total bunker capacity for DMB (MDO)	92	78	67
Bunkertanks dedicated for Low Sulphur DMA (MGO)	86	73	62
Total bunker capacity for DMA (MGO)	86	73	62

**) Vessel shall not mix bunkers from different bunkerings in 1 bunker tank. This may reduce the actual bunker capacity.*

****) Capacity in mt serve as indication only. Actual capacity in mt depending on the specific gravity and temperature of the supplied bunkers.*

Vessel to be solely supplied with fuels as per ISO 8217:2010 or any subsequent amendment thereof. All supplied fuels shall be suitable to enable main propulsion and auxiliary machinery to operate efficiently and without harmful effects and in line with any national and/or international requirements. Fuels to be mineral based products and shall not contain waste lubricants (ULO), chemicals or any other harmful substances and shall be of homogenous and stable nature. Charterers to buy and arrange bunkers only from qualified suppliers and/or from majors and carry out their own quality checks as deemed necessary for their control.

Charterers warrant that whenever bunkers are ordered for the vessel, the order not to put a lien on the vessel and explicitly request "The Products shall not include waste chemicals, waste lubricants and/or other non-fuel components."

BIMCO Bunker Fuel Sulphur Content clause for Time Charter parties 2004 to apply.

If vessel is redelivered in an ECA area, Charterers warrant that vessel will be redelivered with sufficient bunkers suitable for consumption as per the requirements of the relevant ECA area to reach a port or place where suitable bunkers may be supplied.

Vessel participates in fuel testing program. Samples are taken during each fuel from each supplied grade. Costs involved to be equally shared between Owners and Charterers. Vessel shall not consume any supplied fuel without having received full fuel analysis report confirming the fuel's quality.

