



**General**

Built	January-2019	International	<b>GT</b> 6,045.00	<b>NT</b> 3,269.00
Flag	Bahamas	Panama Canal		0.00
Port of Registry	Nassau	Suez Canal		0.00
Callsign	C6DL7			
IMO/Lloyds nr	9795971		<b>Draft</b>	<b>DWAT</b>
Length over all [m]	115.10	Tropical	0.00	0
Beam [m]	18.00	Summer	7.83	7,737
Depth [m]	10.30	Winter	0.00	0
Bowthruster(s)	1			

**Reefer**

Holds	4
Hatches	4
Compartments	12
Minimum Deckheight [m]	2.40 (excl local areas).
Allowable weight of forklift including cargo	maximum 9 mt (Forklift to be equipped with minimum 4 non hard rubber airtyres)
Temperature zones	8
Cooling sections	1A - 1B - 1C - 2A - 2B - 2C - 3A - 3B - 3C - 4A - 4B - 4C
Temperature range [dC]	-25/+5
Air circulations [/hr]	60
Air renewals [/hr]	1.5
USDA equipped	Yes, certificate expired
Controlled Atmosphere	None
Modified Atmosphere	No equipment on board

**Classification Details**

Classification Society Bureau Veritas (BV)  
 Main Class symbols I, +Hull, +Mach  
 Service Notations Refrigerated cargo ship  
 Navigation Notations Unrestricted navigation  
 Additional Class Notations AUT-UMS, MON-SHAFT, unrestricted navigation, INWATERSURVEY, SYS-NEQ-1, SEEMP, REF-Cargo, REFCONT (E), BWT, CLEANSHIP, GREEN PASSPORT, ICE, equipped for the carriage of containers.  
 Machinery +MACH  
 Equivalent Finnish/Swedish  
 Ice Strengthening -

**Reefer Compartment Capacity Breakdown**

	Hold 1		Hold 2		Hold 3		Hold 4		Total	
	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm
A	31,757	314.91	27,993	285.70	27,900	285.87	29,928	310.07	117,578	1,196.55
B	24,586	273.58	24,410	289.67	24,603	289.29	26,664	314.75	100,262	1,167.29
C	23,225	203.77	28,261	284.37	28,358	289.66	24,489	239.47	104,333	1,017.26
<b>Total</b>	<b>79,567</b>	<b>792.26</b>	<b>80,664</b>	<b>859.73</b>	<b>80,861</b>	<b>864.82</b>	<b>81,081</b>	<b>864.28</b>	<b>322,174</b>	<b>3,381.09</b>

Hold 1- 4 Legend

Non insulated Deck, air passes through (aka Spar Deck)

Insulated, air tight Deck or Tanktop

Non Insulated, air tight Deck

**Hatch sizes**

	Hold 1	Hold 2	Hold 3	Hold 4
	l x b	l x b	l x b	l x b
Deck	7.00 x 8.40	7.00 x 8.40	7.00 x 8.40	7.00 x 8.40
A	7.35 x 8.40	7.35 x 8.40	7.35 x 8.40	7.35 x 8.40
B	7.35 x 8.40	7.35 x 8.40	7.35 x 8.40	7.35 x 8.40

Container Carrying Capacity		Max FEU's	Add. TEU's	Max TEU's	Add. FEU's
<u>On Weather Deck and Hatches</u>					
Empty Positions	Standard	72	0	149	0
Max Stackweight	Standard	63	0	149	0
Max Stackweight - Self-sustained	Standard	0	0	0	0
Empty Positions	High Cube	65	0	130	0
Max Stackweight	High Cube	63	0	130	0
Max Stackweight - Self-sustained	High Cube	0	0	0	0
<u>Reefer Hold</u>					
Empty Positions	Standard	0	0	0	0
Max Stackweight	Standard	0	0	0	0
Max Stackweight - Self-sustained	Standard	0	0	0	0

*'Max Stackweight' and 'Max Stackweight - Self-sustained' are the number of laden containers that can be loaded basis the maximum stackweight, calculating 26 mt gross for a laden FEU and 14 mt gross for a laden TEU  
Above figures are as per vessel's technical layout. Actual container intake is subject to master's approval and depending on stability, stackweight and visibility.*

### Standard Voyage Container Carrying Capacity

Nr of High Cube (9.5') Reefers            52  
of which Self-sustained                    0

*'Standard Voyage' = voyage from Panama Canal to Rotterdam, with a full cargo of bananas in the holds and departing with full bunker tanks. Containers on this voyage are considered to weigh 26 mt gross.*

### Reefer Plugs

Nr. of electrical Reefer Plugs            52

### Cargo Gear

8 Derricks x 7.0 mt or 4 x 7.0 mt in Union Purchase

**Bunker Tank Capacities**

	<u>Cbm (100%)</u>	<u>Cbm at max filling level*</u>	<u>mt**</u>
ULS	229	183	182
VLS	528	450	446
<b>Total bunker capacity for RMG380 (IFO380)</b>	<b>757</b>	<b>634</b>	<b>628</b>
ULS	93	71	61
<b>Total bunker capacity for DMA (MGO)</b>	<b>93</b>	<b>71</b>	<b>61</b>

*\*) Vessel shall not mix bunkers from different bunkerings in 1 bunker tank. This may reduce the actual bunker capacity.*

*\*\*\*) Capacity in mt serve as indication only. Actual capacity in mt depending on the specific gravity and temperature of the supplied bunkers.*

*Vessel to be solely supplied with fuels as per ISO 8217:2010 or any subsequent amendment thereof. All supplied fuels shall be suitable to enable main propulsion and auxiliary machinery to operate efficiently and without harmful effects and in line with any national and/or international requirements. Fuels to be mineral based products and shall not contain waste lubricants (ULO), chemicals or any other harmful substances and shall be of homogenous and stable nature. Charterers to buy and arrange bunkers only from qualified suppliers and/or from majors and carry out their own quality checks as deemed necessary for their control.*

*Charterers warrant that whenever bunkers are ordered for the vessel, the order not to put a lien on the vessel and explicitly request "The Products shall not include waste chemicals, waste lubricants and/or other non-fuel components."*

*BIMCO Bunker Fuel Sulphur Content clause for Time Charter parties 2004 to apply.*

*If vessel is redelivered in an ECA area, Charterers warrant that vessel will be redelivered with sufficient bunkers suitable for consumption as per the requirements of the relevant ECA area to reach a port or place where suitable bunkers may be supplied.*

*Vessel participates in fuel testing program. Samples are taken during each fuel from each supplied grade. Costs involved to be equally shared between Owners and Charterers. Vessel shall not consume any supplied fuel without having received full fuel analysis report confirming the fuel's quality.*

