

# SANTA CATHARINA

463,986 cbft / 5,140 sqm / 5,930 pallets



## General

Built	October-2000	International	<b>GT</b>	<b>NT</b>
Flag	Bahamas	Panama Canal	8,597.00	4,737.00
Port of Registry	Nassau	Suez Canal		7,416.00
Callsign	C6RL4			7,464.45
IMO/Lloyds nr	9213777		<b>Draft</b>	<b>DWAT</b>
Length over all [m]	143.00	Tropical	9.42	
Beam [m]	21.80	Summer	9.27	9,635
Depth [m]	13.00	Winter	9.08	9,113
Bowthruster(s)	1			

## Reefer

Holds	4
Hatches	4
Compartments	14
Minimum Deckheight [m]	2.20 (excl local areas).
Allowable weight of forklift including cargo	maximum 9 mt (Forklift to be equipped with minimum 4 non hard rubber airtyres)
Temperature zones	8
Cooling sections	1A - 1B - 2A - 2B - 2C - 2D - 3A - 3B - 3C - 3D - 4A - 4B - 4C - 4D
Temperature range [dC]	-25
Air circulations [/hr]	90
Air renewals [/hr]	4
USDA equipped	Yes, certificate expired
Controlled Atmosphere	CA pre-piped
Modified Atmosphere	No equipment on board



# SANTA CATHARINA

463,986 cbft / 5,140 sqm / 5,930 pallets

## Classification Details

Classification Society	Bureau Veritas (BV)
Main Class symbols	I, +Hull, +MACH
Service Notations	Container ship, Refrigerated cargo ship
Navigation Notations	Unrestricted Navigation
Additional Class Notations	Ice Class 1A, AUT-UMS, MON-SHAFT, +REF-CARGO-AIRCONT
Machinery	+MACH
Equivalent Finnish/Swedish	
Ice Strengthening	IA

## Reefer Compartment Capacity Breakdown

	Hold 1		Hold 2		Hold 3		Hold 4		Total	
	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm
A	24,553	247.30	40,289	425.00	41,142	443.80	40,528	444.60	146,512	1,560.70
B	16,700	185.80	35,049	406.30	38,217	446.20	38,176	453.90	128,142	1,492.20
C			30,233	341.70	37,879	449.30	35,043	396.30	103,155	1,187.30
D			23,324	231.30	34,794	380.00	28,059	288.80	86,177	900.10
<b>Total</b>	<b>41,253</b>	<b>433.10</b>	<b>128,895</b>	<b>1,404.30</b>	<b>152,032</b>	<b>1,719.30</b>	<b>141,806</b>	<b>1,583.60</b>	<b>463,986</b>	<b>5,140.30</b>

Hold 1- 4 Legend

Non insulated Deck, air passes through (aka Spar Deck)

Insulated, air tight Deck or Tanktop

Non Insulated, air tight Deck

## Hatch sizes

	Hold 1	Hold 2	Hold 3	Hold 4
	l x b	l x b	l x b	l x b
Deck	7.00 x 8.00	12.60 x 8.00	12.60 x 8.00	12.60 x 8.00
A		-		
B		-		
C		-		



# SANTA CATHARINA

463,986 cbft / 5,140 sqm / 5,930 pallets

Container Carrying Capacity		Max FEU's	Add. TEU's	Max TEU's	Add. FEU's
<u>On Weather Deck and Hatches</u>					
Empty Positions	Standard	118	0	227	0
Max Stackweight	Standard	111	0	150	24
Max Stackweight - Selfsustained	Standard	111	0	150	24
Empty Positions	High Cube	115	0	227	0
Max Stackweight	High Cube	108	0	150	24
Max Stackweight - Selfsustained	High Cube	108	0	150	24
<u>Reefer Hold</u>					
Empty Positions	Standard	36	6	78	0
Max Stackweight	Standard	36	6	78	0
Max Stackweight - Selfsustained	Standard	36	6	78	0
Empty Positions	High Cube	27	6	78	0
Max Stackweight - Selfsustained	High Cube	27	6	78	0

'Max Stackweight' and 'Max Stackweight - Selfsustained' are the number of laden containers that can be loaded basis the maximum stackweight, calculating 26 mt gross for a laden FEU and 14 mt gross for a laden TEU

Above figures are as per vessel's technical layout. Actual container intake is subject to master's approval and depending on stability, stackweight and visibility.

## Standard Voyage Container Carrying Capacity

Nr of High Cube (9.5') Reefers      102  
of which Selfsustained                102

'Standard Voyage' = voyage from Panama Canal to Rotterdam, with a full cargo of bananas in the holds and departing with full bunker tanks. Containers on this voyage are considered to weigh 26 mt gross.

## Reefer Plugs

Nr. of electrical Reefer Plugs        135

## Cargo Gear

2 Cranes x 40.0 mt  
2 Cranes x 8.0 mt



# SANTA CATHARINA

463,986 cbft / 5,140 sqm / 5,930 pallets

## Bunker Tank Capacities

	<u>Cbm (100%)</u>	<u>Cbm at max filling level*</u>	<u>mt**</u>
VLS	1,558	1,456	1,443
<b>Total bunker capacity for RMG380 (IFO380)</b>	<b>1,558</b>	<b>1,456</b>	<b>1,443</b>
ULS	151	144	122
<b>Total bunker capacity for DMA (MGO)</b>	<b>151</b>	<b>144</b>	<b>122</b>

\*) Vessel shall not mix bunkers from different bunkerings in 1 bunker tank. This may reduce the actual bunker capacity.

\*\*) Capacity in mt serve as indication only. Actual capacity in mt depending on the specific gravity and temperature of the supplied bunkers.

Vessel to be solely supplied with fuels minimal as per ISO 8217:2017 or any subsequent amendment thereof. All supplied fuels shall be suitable to enable main propulsion and auxiliary machinery to operate efficiently and without harmful effects and in line with any national and/or international requirements. Fuels to be mineral based products and shall not contain waste lubricants (ULO), chemicals or any other harmful substances and shall be of homogenous and stable nature. Charterers to buy and arrange bunkers only from qualified suppliers and/or from majors and carry out their own quality checks as deemed necessary for their control. Bunkers supplied in Amsterdam/Velsen/Beverwijk/IJmuiden region must have an origin from a major supplier (BP/Shell/Exxon); products sourced from Glencore or Trafigura are explicitly excluded.

Charterers warrant that whenever bunkers are ordered for the vessel, the order not to put a lien on the vessel and explicitly request "The Products shall not include waste chemicals, waste lubricants and/or other non-fuel components."

BIMCO Bunker Fuel Sulphur Content clause for Time Charter parties 2004 to apply.


If vessel is redelivered in an ECA area, Charterers warrant that vessel will be redelivered with sufficient bunkers suitable for consumption as per the requirements of the relevant ECA area to reach a port or place where suitable bunkers may be supplied.

Vessel participates in fuel testing program. Samples are taken during each fuel from each supplied grade. Costs involved to be equally shared between Owners and Charterers. Vessel shall not consume any supplied fuel without having received full fuel analysis report confirming the fuel's



# SANTA CATHARINA

463,986 cbft / 5,140 sqm / 5,930 pallets



## General Remarks

- Pallet Intake figures are indication only. The figures are based on a stowage factor of 1.32 pallet/sqm in reefer holds, full load of reefer containers based on the standard voyage with 20 pallets in each container

