



General

Built	December-2001	International	GT 7,207.00	NT 2,441.00
Flag	Bahamas	Panama Canal		6,176.00
Port of Registry	Nassau	Suez Canal		6,576.00
Callsign	C6GL3			
IMO/Lloyds nr	9238703		Draft	DWAT
Length over all [m]	132.90	Tropical	8.25	7,877
Beam [m]	18.80	Summer	8.08	7,749
Depth [m]	10.28	Winter	7.91	7,215
Bowthruster(s)	1 x 368kW			

Reefer

Holds	4
Hatches	4
Compartments	14
Minimum Deckheight [m]	2.20 (excl local areas).
Allowable weight of forklift including cargo	maximum 5 mt (Forklift to be equipped with minimum 4 non hard rubber airtyres)
Temperature zones	6
Cooling sections	1A - 1B - 1C - 2A - 2B - 2C - 3A - 3B - 3C - 3D - 4A - 4B - 4C - 4D
Temperature range [dC]	-25/+12
Air circulations [/hr]	90
Air renewals [/hr]	2
USDA equipped	Yes, certificate expired
Controlled Atmosphere	None
Modified Atmosphere	No equipment on board

Classification Details

Classification Society	Bureau Veritas (BV)
Main Class symbols	I, +Hull, +Mach
Service Notations	Refrigerated cargo ship
Navigation Notations	Unrestricted Navigation
Additional Class Notations	+AUT-UMS, +REF-CARGO -QUICKFREEZE
Machinery	+MACH

Reefer Compartment Capacity Breakdown

	Hold 1		Hold 2		Hold 3		Hold 4		Total	
	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm
A	24,579	216.10	18,975	201.00	19,406	201.00	16,771	173.00	79,731	791.10
B	15,235	150.30	29,234	332.80	31,872	384.90	25,907	333.00	102,247	1,201.00
C	9,892	117.80	26,020	286.80	33,203	377.30	28,697	324.00	97,811	1,105.90
D					30,960	338.00	25,688	248.80	56,648	586.80
Total	49,705	484.20	74,228	820.60	115,441	1,301.20	97,063	1,078.80	336,437	3,684.80

Hold 1- 4 Legenda

Non insulated Deck, air passes through (aka Spar Deck)

Insulated, air tight Deck or Tanktop

Non Insulated, air tight Deck

Hatch sizes

	Hold 1	Hold 2	Hold 3	Hold 4
	l x b	l x b	l x b	l x b
Deck	10.00 x 7.97	10.00 x 9.37	10.00 x 9.37	10.00 x 9.37
A	10.00 x 6.21	10.00 x 8.80	10.00 x 8.80	10.00 x 8.80
B	8.13 x 4.98	10.00 x 8.80	10.00 x 8.80	10.00 x 8.80
C		-	10.00 x 8.80	10.00 x 8.80

Container Carrying Capacity		Max FEU's	Add. TEU's	Max TEU's	Add. FEU's
<u>On Weather Deck and Hatches</u>					
Empty Positions	Standard	18	0	8	0
Max Stackweight	Standard	18	0	8	0
Max Stackweight - Selfsustained	Standard	18	0	0	0
<u>Reefer Hold</u>					
Empty Positions	Standard	0	0	0	0
Max Stackweight	Standard	0	0	0	0
Max Stackweight - Selfsustained	Standard	0	0	0	0

'Max Stackweight' and 'Max Stackweight - Selfsustained' are the number of laden containers that can be loaded basis the maximum stackweight, calculating 26 mt gross for a laden FEU and 14 mt gross for a laden TEU

Above figures are as per vessel's technical layout. Actual container intake is subject to master's approval and depending on stability, stackweight and visibility.

Standard Voyage Container Carrying Capacity

Nr of High Cube (9.5') Reefers 0
of which Selfsustained 0


'Standard Voyage' = voyage from Panama Canal to Rotterdam, with a full cargo of bananas in the holds and departing with full bunker tanks. Containers on this voyage are considered to weigh 26 mt gross.

Reefer Plugs


Nr. of electrical Reefer Plugs 22

Cargo Gear


4 Cranes x 6.0 mt




CUB. PRINCIPAL
CUB. Nº 4
A 10280 SOBRE L. BASE



CUB. INFERIOR
CUB. Nº 3
A 1366/7585 SOBRE L. BASE



CUB. BAJA
CUB. Nº 2
A 4440/4388 SOBRE L. BASE



DOBLE FONDO
CUB. Nº 1
A 1490 SOBRE L. BASE

