



## General

Built	June-1996	International	<b>GT</b> 5,918.00	<b>NT</b> 3,177.00
Flag	Bahamas	Panama Canal		5,088.00
Port of Registry	Nassau	Suez Canal		4,294.14
Callsign	C6GE7			
IMO/Lloyds nr	9127928		<b>Draft</b>	<b>DWAT</b>
Length over all [m]	133.92	Tropical	8.07	8,250
Beam [m]	16.31	Summer	7.91	7,947
Depth [m]	11.90	Winter	7.74	7,647
Bowthruster(s)	1			

## Reefer

Holds	4
Hatches	4
Compartments	16
Minimum Deckheight [m]	2.20 (excl local areas).
Allowable weight of forklift including cargo	maximum 5 mt (Forklift to be equiped with minimum 4 non hard rubber airtyres)
Temperature zones	8
Cooling sections	1A B - 1C D - 2A B - 2C D - 3A B - 3C D - 4A B - 4C D
Temperature range [dC]	-25/+12
Air circulations [/hr]	90
Air renewals [/hr]	2
USDA equipped	Yes, certificate expired
Controlled Atmosphere	CA pre-piped
Modified Atmosphere	No equipment on board

Classification Details

Classification Society	Bureau Veritas (BV)
Main Class symbols	I, +HULL, +MACH
Service Notations	+Refrigerated cargo ship
Navigation Notations	Unrestricted Navigation
Additional Class Notations	+AUT-UMS,MON-SHAFT, +REF-CARGO
Machinery	+MACH
Equivalent Finnish/Swedish	
Ice Strenghtening	-

Reefer Compartment Capacity Breakdown

	Hold 1		Hold 2		Hold 3		Hold 4		Total	
	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm	Cbft	Sqm
A	27,165	302.10	30,217	351.50	27,932	323.20	28,344	328.30	113,658	1,305.10
B	23,256	270.50	28,702	351.10	26,458	324.10	26,589	324.70	105,005	1,270.40
C	18,568	213.20	27,896	346.10	25,987	324.30	23,579	287.30	96,030	1,170.90
D	15,778	176.60	27,511	326.10	26,246	313.10	14,242	173.90	83,777	989.70
Total	84,767	962.40	114,326	1,374.80	106,623	1,284.70	92,754	1,114.20	398,470	4,736.10

Hold 1- 4 Legenda

Non insulated Deck, air passes through (aka Spar Deck)	Insulated, air tight Deck or Tanktop
Non Insulated, air tight Deck	

Hatch sizes

	Hold 1	Hold 2	Hold 3	Hold 4
	l x b	l x b	l x b	l x b
Deck	8.10 x 8.08	8.10 x 8.08	8.10 x 8.08	8.10 x 8.08
A		-		
B		-		
C		-		

Container Carrying Capacity		Max FEU's	Add. TEU's	Max TEU's	Add. FEU's
<u>On Weather Deck and Hatches</u>					
Empty Positions	Standard	45	0	90	0
Max Stackweight	Standard	27	0	54	0
Empty Positions	High Cube	45	0	90	0
Max Stackweight	High Cube	27	0	54	0
<u>Reefer Hold</u>					
Empty Positions	Standard	0	0	40	0
Empty Positions	High Cube	0	0	40	0

'Max Stackweight' and "Max Stackweight - Selfsustained' are the number of laden containers that can be loaded basis the maximum stackweight, calculating 26 mt gross for a laden FEU and 14 mt gross for a laden TEU  
Above figures are as per vessel's technical layout. Actual container intake is subject to master's approval and depending on stability, stackweight and visibility.

Standard Voyage Container Carrying Capacity

Nr of High Cube (9.5') Reefers 17  
of which Selsustained 0

'Standard Voyage' = voyage from Panama Canal to Rotterdam, with a full cargo of bananas in the holds and departing with full bunker tanks. Containers on this voyage are considered to weigh 26 mt gross.

Reefer Plugs

Nr. of electrical Reefer Plugs 25

Cargo Gear

4 Cranes x 7.0 mt

Bunker Tank Capacities

	Cbm (100%)	Cbm at max filling level*	mt**
Overflow/Settling/Daytanks for RMG380 (IFO380)	68	58	57
VLS	920	833	826
Total bunker capacity for RMG380 (IFO380)	989	891	883
ULS	87	74	62
Total bunker capacity for DMA (MGO)	87	74	62
<p>*) Vessel shall not mix bunkers from different bunkerings in 1 bunker tank. This may reduce the actual bunker capacity.</p> <p>**) Capacity in mt serve as indication only. Actual capacity in mt depending ao on the specifice gravity and temperature of the supplied bunkers.</p> <p>Vessel to be solely supplied with fuels minimal as per ISO 8217:2017 or any subsequent amendment thereof. All supplied fuels shall be suitable to enable main propulsion and auxiliary machinery to operate efficiently and without harmful effects and in line with any national and/or international requirements. Fuels to be mineral based products and shall not contain waste lubricants (ULO), chemicals or any other harmful substances and shall be of homogenous and stable nature. Charterers to buy and arrange bunkers only from qualified suppliers and/or from majors and carry out their own quality checks as deemed necessary for their control. Bunkers supplied in Amsterdam/Velsen/Beverwijk/IJmuiden region must have an origin from a major supplier (BP/Shell/Exxon).</p> <p>Charterers warrant that whenever bunkers are ordered for the vessel, the order not to put a lien on the vessel and explicitly request "The Products shall not include waste chemicals, waste lubricants and/or other non-fuel components."</p> <p>BIMCO Bunker Fuel Sulphur Content clause for Time Charter parties 2004 to apply.</p> <p>If vessel is redelivered in an ECA area, Charterers warrant that vessel will be redelivered with sufficient bunkers suitable for consumption as per the requirements of the relevant ECA area to reach a port or place where suitable bunkers may be supplied.</p> <p>Vessel participates in fuel testing program. Samples are taken during each fuel from each supplied grade. Costs involved to be equally shared between Owners and Charterers. Vessel shall not consume any supplied fuel without having received full fuel analysis report confirming the fuel's</p>			

