

	20' Standard Dry		20' Open top		20' Flat Rack	
Weight	kg	lb	kg	lb	kg	lb
Tare Weight	2,200	4,850	2,460	5,420	2,980	6570
Payload	28,280	62,350	21,540	47,500	27,500	60630
Gross weight	30,480	67,200	24,000	52,910	30,480	67200
External Dimensions	m	ft in	m	ft in	m	ft in
Length	6.06	20' 0"	6.06	20' 0"	6.06	20' 0"
Width	2.44	8' 0"	2.44	8' 0"	2.44	8' 0"
Height	2.59	8' 6"	2.59	8' 6"	2.59	8' 6"
Internal Dimensions	m	ft in	m	ft in	m	ft in
Length	5.90	19' 4"	5.89	19' 4"	5.93	19' 5.5"
Width	2.35	7' 8"	2.35	7' 8.6"	2.12	6' 11.5"
Height	2.39	7' 10"	2.33	7' 7.7"	2.16	7' 1.2"

**The specifications used are general descriptions.
Measurements for actual units may vary.**

	40' Standard Dry		40' HC Dry		40' Standard Reefer		40' HC Reefer		40' Open top		40' Flat Rack	
Weight	kg	lb	kg	lb	kg	lb	kg	lb	kg	lb	kg	lb
Tare Weight	3,640	8,030	4,880	10,760	5,100	11,240	4,870	10,740	4,100	9,039	5,450	12,015
Payload	28,860	63,620	27,600	60,880	25,380	55,960	29,130	64,230	26,380	58,161	39,550	87,185
Gross weight	32,500	71,650	32,480	71,640	30,480	67,200	34,000	74,970	30,480	67,200	45,000	99,200
External Dimensions	m	ft in	m	ft in	m	ft in	m	ft in	m	ft in	m	ft in
Length	12.19	40' 0"	12.19	40' 0"	12.19	40' 0"	12.19	40' 0"	12.19	40' 0"	12.19	40' 0"
Width	2.44	8' 0"	2.44	8' 0"	2.44	8' 0"	2.44	8' 0"	2.44	8' 0"	2.44	8' 0"
Height	2.59	8' 6"	2.90	9' 6"	2.59	8' 6"	2.90	9' 6"	2.59	8' 6"	2.59	8' 6"
Internal Dimensions	m	ft in	m	ft in	m	ft in	m	ft in	m	ft in	m	ft in
Length	12.03	39' 5.5"	12.03	39' 5.5"	11.58	37' 11.7"	11.59	38' 0.12"	12.03	39' 5.5"	12.08	39' 7.5"
Width	2.35	7' 8.6"	2.35	7' 8.6"	2.25	7' 4.6"	2.29	7' 6.1"	2.35	7' 8.6"	2.23	7' 3.8"
Height	2.39	7' 10"	2.70	8' 10"	2.22	7' 3.4"	2.54	8' 4"	2.33	7' 7.7"	1.95	6' 4.8"